



PRODUCT DATA SHEET

D9264

Werlatone® Mismatch Tolerant® High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide **Werlatone®** designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

Features:

High Power Wide Bandwidths Small Size High Isolation Custom Designs Available

Electrical Specifications:

Frequency: 20 - 1000 MHz
Power: 1000 W CW
Insertion Loss: 0.8 dB Max.
VSWR: 1.40:1 Max.
Phase Balance: $\pm 5^\circ$ Max.
Amplitude Balance: 0.3 dB Max.
Isolation: 18 dB Min.

Mechanical Specifications:

Type: Connectorized
Material: Aluminum 6061-T6
Surface Finish: Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available
Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C
Weight: 5.25 lbs.
Size: 6.5 x 6.25 x 2.25"

Connector Configurations:

Model	Sum Port (J1)	Input/Output (J2)	Input/Output (J3)
D9264-10	N Female	N Female	N Female
D9264-20	7/16 Female	N Female	N Female
D9264-40	SC Female	SC Female	SC Female
D9264-41	SC Female	N Female	N Female

When specified, Werlatone® High Power Combiners and RF Dividers will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.




PRODUCT DATA SHEET


D9264

Performance Data (Specifications subject to change without notice):


Insertion Loss:




VSWR:



Isolation:





Phase Balance:



RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
 This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISIONS			
REV.	REVISION RECORD	DATE	APPROVED
-	INITIAL RELEASE	6/11/2012	



		UNLESS OTHERWISE SPECIFIED		DATE	6/11/2012		 WERLATONE SINCE 1965	17 Jon Barrett Rd Patterson, NY 12563		
		INTERPRET DRAWING IN ACCORDANCE WITH MIL-STD-100		DWG	NO					
		DIMENSIONS ARE IN INCHES		DATE			OUTLINE			
		DIMENSIONS ARE IN INCHES		DATE						
		TOLERANCES		DATE			SIZE CAGE CODE DWG NO	REV		
		ANGLES ± 3°		DATE						
		3 PL ± .015		DATE			SCALE	SHEET 1 OF 1		
		REMOVE ALL BURRS AND SHARP EDGES R/L MAX		DATE						
		CONCENTRICITY MAX .004 .002 F/M		DATE						
		MACHINE TOOL MISMATCH .003 MAX		DATE						
		THIRD ANGLE PROJECTION								