



PRODUCT DATA SHEET

C7325

4-Port Dual Directional Coupler employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

Frequency: 0.1 - 250 MHz
Power: 1000 W CW
Coupling: 50 ± 1.0 dB Max.
Insertion Loss: 0.15 dB Max.
Flatness: ± 0.5 dB Max.
VSWR (ML): 1.15:1 Max.
Directivity: 20 dB Min.

Mechanical Specifications:

Type: Connectorized
Material: Aluminum 6061-T6
Surface Finish: Chem. Film Per MIL-DTL-5541F
Type I Class 3 (Yellow Iridite)
RoHS Compliant Available
Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C
Humidity: 95% Non-Condensing
Size: 6.0 x 2.2 x 2.2"

Connector Configurations:

Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C7325-10	N Female	N Female	N Female	N Female
C7325-12	N Female	N Female	SMA	SMA
C7325-13	N Female	N Female	BNC	BNC
C7325-20	7/16 Female	7/16 Female	N Female	N Female
C7325-64	HN Female	HN Female	BNC	BNC

Werlatone® Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.



WERLATONE

Model C7325

Connectorized Directional Couplers




PRODUCT DATA SHEET


C7325

Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:



Directivity:




Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
A	ECN 3334	6/25/03	RH
B	ECN 4036	8/18/06	MJ
C	ECN 8543	1/31/2014	SC
D	ECN 8618	4/2/2014	SC
E	ECN 9696	5/14/2019	RB



- NOTES: UNLESS OTHERWISE SPECIFIED**
- 1. MATERIAL: ALUMINUM 6061-T6**
 - 2. FINISH: CHEM FILM PER MIL-DTL-5541F TYPE I CLASS 3 (YELLOW IRIDITE)**
 - 3. CONNECTORS:**
 - J1-J2: N FEMALE**
 - J3-J4: SMA FEMALE**

UNLESS OTHERWISE SPECIFIED INTERPRET DRAWING IN ACCORDANCE WITH DIMENSIONS PER ASME Y14.5-2009 PARENT/CHILD DIMS FOR BEST FIT ONLY DIMENSIONS ARE IN INCHES DIMENSIONAL LIMITS APPLY BEFORE PROCESSES TOLERANCES: ANGLES = $\pm$ 1° 3 PL. $\pm$.005 [13] 2 PL. $\pm$.015 [30] REMOVE ALL BURRS AND SHARP EDGES 8.01 MAX CONCENTRICITY MACHINED DIA. $\pm$.002 PAK MACHINE TOOL RESTRAINT .001 MAX		DWN DATE 5/14/2019 SD DATE CHR DATE CS DATE 5/14/2019 ENGR DATE REGR DATE QA DATE RLSE DATE	 WERLATONE SINCE 1965 TITLE <h1>OUTLINE</h1> SIZE CAGE CODE DWG NO SCALE 1:25 10914-500	17 Jon Barrett Rd Patterson, NY 12563 SHEET 1 OF 1
NEXT ASSY USED ON APPLICATION	THIRD ANGLE PROJECTION			

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc. Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com