WERLATONE

Model C5964
Connectorized Directional Couplers



PRODUCT DATA SHEET **C5964**

4-Port Dual Directional Coupler employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem,
providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward
and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

Frequency:	0.01 - 1000 MHz
Power:	50 W CW
Coupling:	30 ± 1.0 dB Max.
Insertion Loss:	1.2 dB Max.
Flatness:	± 0.5 dB Max.
VSWR (ML):	1.30:1 Max.
Directivity:	20 dB Min.

Mechanical Specifications:

Type:	Connectorized
Material:	Aluminum 6061-T6
Suface Finish:	Chem. Film Per MIL-DTL-5541F Type I Class 3 (Yellow Iridite) RoHS Compliant Available
Operating Temperature:	-55°C to +75°C
Storage Temperature:	-60°C to +85°C
Humidity:	95% Non-Condensing
Size:	5.2 x 2.28 x 1.69''

Connector Configurations:

Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C5964-10	N Female	N Female	N Female	N Female
C5964-12	N Female	N Female	SMA	SMA
C5964-13	N Female	N Female	BNC	BNC
C5964-102	SMA	SMA	SMA	SMA
C5964-610	N Female	N Male	N Female	N Female
C5964-714	N Male	N Female	N Female	N Female


Werlatone® Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com




Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:




Directivity:



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

Werlatone, Inc.All Rights Reserved

RESTRICTION ON USE, DUPLICATION OR
DISCLOSURE OF PROPRIETARY INFORMATION
This document contains proprietary information
which is the sole property of Werlatone, Inc.



REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
A	ECN 9696	11/28/18	RB

NOTES: UNLESS OTHERWISE SPECIFIED

1. **MATERIAL: ALUMINUM 6061-T6**
2. **FINISH: CHEM FILM PER MIL-DTL-5541F TYPE I CLASS 3 (YELLOW IRIDITE)**
3. **CONNECTORS:**
   J1, J2: N FEMALE
   J3, J4: N FEMALE

NEXT ASSY	USED ON	UNLESS OTHERWISE SPECIFIED: INTERPRET DRAWING IAW MIL-STD-100 · DIMENSIONING PER ASME Y14.5M-2009 · PARENTHETICAL INFO FOR REF ONLY · DIMENSIONS ARE IN INCHES · DIMENSIONAL LIMITS APPLY BEFORE PROCESSES · TOLERANCES: ANGLES ± 2° 3 PL ± .005 [.13] 2 PL ± .015 [.38] · REMOVE ALL BURRS AND SHARP EDGES R.01 MAX · CONCENTRICITY MACHINED DIA: .002 FIM · MACHINE TOOL MISMATCH .003 MAX	DWN SD 2/11/2019	WERLATONE| SINCE 1965	17 Jon Barrett Rd Patterson, NY 12563
APPLICATION			CHK CS 2/11/2019	TITLE: OUTLINE	
		THIRD ANGLE PROJECTION	ENGR CS 2/27/2002	SIZE B · CAGE CODE · DWG NO 10407-505	REV A
			MFGR	SCALE 1:1.5	SHEET 1 OF 1
			QA		
			RLSE		

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com