

## PRODUCT DATA SHEET

C6099

**4-Port Dual Directional Coupler** employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

### Features:

High Power      Wide Bandwidths      Small Size      Flat Coupling      Custom Designs Available

### Electrical Specifications:

Frequency: 500 - 1000 MHz  
Power: 500 W CW  
Coupling:  $40 \pm 1.0$  dB Max.  
Insertion Loss: 0.2 dB Max.  
Flatness:  $\pm 0.25$  dB Max.  
VSWR (ML): 1.15:1 Max.  
Directivity: 20 dB Min.

### Mechanical Specifications:

Type: Connectorized  
Material: Aluminum 6061-T6  
Surface Finish: Chem. Film Per MIL-DTL-5541F  
Type I Class 3 (Yellow Iridite)  
RoHS Compliant Available  
Operating Temperature: -55°C to +75°C  
Storage Temperature: -60°C to +85°C  
Humidity: 95% Non-Condensing  
Size: 3.0 x 3.0 x 1.09"

### Connector Configurations:

| Model     | Input (J1) | Output (J2) | Fwd (J3) | Rev (J4) |
|-----------|------------|-------------|----------|----------|
| C6099-10  | N Female   | N Female    | N Female | N Female |
| C6099-12  | N Female   | N Female    | SMA      | SMA      |
| C6099-13  | N Female   | N Female    | BNC      | BNC      |
| C6099-302 | TNC Female | TNC Female  | SMA      | SMA      |


**Werlatone®** Broadband Dual, Uni, and Bi Directional RF Couplers are designed to tolerate the most stringent operating conditions associated with military and EMC testing environments. Many of our RF Directional Couplers, designated Mismatch Tolerant®, will operate continuously, at rated power, into a severe load mismatch condition. Our multi-octave Directional Couplers maintain exceptional coupling flatness, directivity, VSWR, and insertion loss.



# WERLATONE

Model C6099

Connectorized Directional Couplers




## PRODUCT DATA SHEET


C6099

### Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Insertion Loss:




Directivity:



**Restriction on use, duplication, or disclosure of proprietary information.** This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

RESTRICTION ON USE, DUPLICATION OR  
DISCLOSURE OF PROPRIETARY INFORMATION  
This document contains proprietary information  
which is the sole property of Werlatone, Inc.



| REVISION HISTORY |                 |          |          |
|------------------|-----------------|----------|----------|
| REV.             | REVISION RECORD | DATE     | APPROVED |
| A                | ECN 9696        | 11/27/18 | RB       |

**NOTES: UNLESS OTHERWISE SPECIFIED**

- MATERIAL: ALUMINUM 6061-T6**
- FINISH: CHEM FILM PER MIL-DTL\_5541F TYPE I CLASS 3 (YELLOW IRIDITE)**

| UNLESS OTHERWISE SPECIFIED                  |  | OWN  | DATE     | WERLATONE SINCE 1965  |  | 17 Jon Barrett Rd<br>Patterson, NY 12563 |
|---------------------------------------------|--|------|----------|-----------------------|--|------------------------------------------|
| • INTERPRET DRAWING JAW MIL-STD-100         |  | RH   | 7/5/2001 | TITLE                 |  | REV                                      |
| • DIMENSIONING FOR ASME Y14.5M-2009         |  | CHK  | DATE     |                       |  |                                          |
| • PARENTHETICAL INFO FOR REF ONLY           |  | ENGR | DATE     | OUTLINE               |  | A                                        |
| • DIMENSIONS ARE IN INCHES                  |  | MJ   | 7/5/2001 |                       |  |                                          |
| • DIMENSIONAL LIMITS APPLY BEFORE PROCESSES |  | MPGR | DATE     | SIZE CAGE CODE DWG NO |  | SHEET 1 OF 1                             |
| • TOLERANCES:                               |  | QA   | DATE     |                       |  |                                          |
| • ANGLES: ± 2°                              |  | ELSE | DATE     | SCALE                 |  | 1:1                                      |
| • 3 PL. ± .005 [1.3]                        |  |      |          |                       |  |                                          |
| • 2 PL. ± .015 [1.3]                        |  |      |          | APPLICATION           |  | THIRD ANGLE PROJECTION                   |
| • REMOVE ALL BURRS AND SHARP EDGES R.01 MAX |  |      |          |                       |  |                                          |
| • CONCENTRICITY MACHINED DIA: .002 FIM      |  |      |          | NEXT ASSY USED ON     |  | REV                                      |
| • MACHINE TOOL MISMATCH: .003 MAX           |  |      |          |                       |  |                                          |

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.  
Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com