

PRODUCT DATA SHEET

C6265

4-Port Dual Directional Coupler employs two, 3-Port Uni-Directional Couplers, internally connected, in tandem, providing measurement of both forward and reverse power. Ideal for simultaneously monitoring a system's forward and reverse power and for reflectometer measurements. Unlike the Bi-Directional Coupler, the directivity of the Dual Directional Coupler is unaffected by the loads on the coupled ports.

Features:

High Power Wide Bandwidths Small Size Flat Coupling Custom Designs Available

Electrical Specifications:

Frequency: 500 - 3000 MHz
Power: 500 W CW
Coupling: 50 ± 1.0 dB Max.
Flatness: ± 0.75 dB Max.
Insertion Loss: 0.2 dB Max.
VSWR (ML): 1.30:1 Max.
Directivity: 20 dB Min.

Mechanical Specifications:

Type: Connectorized
Material: Aluminum 6061-T6
Surface Finish: Chem. Film Per MIL-DTL-5541F
Type I Class 3 (Yellow Iridite)
RoHS Compliant Available
Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C
Humidity: 95% Non-Condensing
Size: 3.0 x 3.0 x 1.09"


Connector Configurations:

Model	Input (J1)	Output (J2)	Fwd (J3)	Rev (J4)
C6265-10	N Female	N Female	N Female	N Female
C6265-12	N Female	N Female	SMA	SMA
C6265-20*	7/16 Female	7/16 Female	N Female	N Female
C6265-22*	7/16 Female	7/16 Female	SMA	SMA
C6265-23*	7/16 Female	7/16 Female	BNC	BNC
C6265-41	SC Female	SC Female	N Female	N Female
C6265-43	SC Female	SC Female	SMA	SMA
C6265-627*	7/16 Female	7/16 Male	N Female	N Female
C6265-714	N Male	N Female	N Female	N Female
C6265-727*	7/16 Male	7/16 Female	N Female	N Female
C6265-728*	7/16 Male	7/16 Female	SMA	SMA

(7/16 Mainline Connector option increases case height to 1.59")

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com




PRODUCT DATA SHEET


C6265

Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:




Insertion Loss:



Directivity:



RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
This document contains proprietary information which is the sole property of Werlatone, Inc.



REVISION HISTORY			
REV.	REVISION RECORD	DATE	APPROVED
A	ECN 9696	11/27/18	RB

NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL: ALUMINUM 6061-T6
2. FINISH: CHEM FILM PER MIL-DTL 5541F TYPE I CLASS 3 (YELLOW IRIDITE)

		UNLESS OTHERWISE SPECIFIED		OWN	DATE	 WERLATONE® SINCE 1965	17 Jon Barrett Rd Patterson, NY 12568			
NEXT ASSY USED ON	APPLICATION	<ul style="list-style-type: none">• INTERPRET DRAWING AS PER MIL-STD-100• DIMENSIONING PER ASME Y14.5-2009• DIMENSIONAL INFO FOR REF ONLY• DIMENSIONS ARE IN INCHES• DIMENSIONAL LIMITS APPLY BEFORE PROCESSES• TOLERANCES:<ul style="list-style-type: none">ANGLES ± °Ø R, ± .005 [13]± P, ± .025 [18]• REMOVE ALL MARKS AND SHARP EDGES R.01 MAX• CONDUCTIVITY MACHINED SUR. 402 FPM• MACHINE TOOL, REWORKING .002 MAX		RH	7/5/2001		OUTLINE SIZE CAGE CODE DWG NO <div>10379-505</div>	R1	SHEET 1 OF 1	
				CHK	DATE					TITLE
				BNGR	7/5/2001					
				MJ	DATE					
				QA	DATE					
				RLSE	DATE					
		THIRD ANGLE PROJECTION 		SCALE		1:1				

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc. Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com