

PRODUCT DATA SHEET

D9194

Werlatone® Mismatch Tolerant® High Power Broadband RF Combiners and Dividers will operate into High Load VSWR Conditions, for extended periods, without damage. With extensive experience as a supplier to military platforms worldwide **Werlatone®** designs its High Power Broadband Combiners, Power Dividers, and N-Way Combiners for proper operation in the most stringent operating conditions.

Features:

High Power Wide Bandwidths Small Size Custom Designs Available

Electrical Specifications:

Frequency:	2305 - 2360 MHz
Power:	1000 W CW
Insertion Loss:	0.2 dB Max.
VSWR:	1.15:1 Max.
Phase Balance:	$\pm 5^\circ$ Max.
Amplitude Balance:	0.2 dB Max.
Isolation:	Non-Isolated


Mechanical Specifications:

Type:	Connectorized
Material:	Aluminum 6061-T6
Surface Finish:	Chem. Film Per MIL-DTL-5541F Type II Class 3 (RoHS Compliant Film)
Operating Temperature:	-55°C to +75°C
Storage Temperature:	-60°C to +85°C
Size:	RADIAL 4.02 x 3.57" NOM

Connector Configurations:

Model	Sum Port (J17)	Input/Output (J1-J16)
D9194R-20	7/16 Female Long Barrel- Silver Plated	N Female- Silver Plated
D9194R-20RT	7/16 Female Long Barrel- Silver Plated	Right Angle N Female - Silver Plated

When specified, Werlatone® High Power Combiners and RF Dividers will tolerate full input failures on adjacent port(s). This insures that remaining transmitter(s) may continue to operate until the amplifier system can be properly shut down for maintenance. Choose your specific connector configuration from a list of options. Additional connector configurations for our High Power RF Combiners/Dividers, Non-Coherent Combiners, and N-Way Combiners are available upon request.




PRODUCT DATA SHEET


D9194

Performance Data (Specifications subject to change without notice):

Insertion Loss:




VSWR:



Since 1965:





Phase Balance:



RESTRICTION ON USE, DUPLICATION OR DISCLOSURE OF PROPRIETARY INFORMATION
 This document contains proprietary information which is the sole property of Werlatone, Inc.

REVISIONS			
REV.	REVISION RECORD	DATE	APPROVED
-	INITIAL RELEASE	12/12/2012	SC



UNLESS OTHERWISE SPECIFIED INTERPRET DRAWING IN ACCORDANCE WITH MIL-STD-100 DIMENSIONS ARE IN INCHES DIMENSIONAL UNITS APPLY BEFORE PROCESSES TOLERANCES: ANGLES ± 3° 3 PL ± .005 REMOVE ALL BURRS AND SHARP EDGES R/L MAX CONCENTRICITY MAXIMUM .004 INCHES MACHINE TOOL MISMATCH .003 MAX		DATE	12/12/2012	17 Jon Barrett Rd Patterson, NY 12563
		CHK	SC	
		ENGR		
		INPR		
NEXT ASSY USED ON APPLICATION		DATE		
		QA		
		REL		
THIRD ANGLE PROJECTION		DATE		
TITLE OUTLINE		DATE		
SCALE 1:2		DATE		
SHEET 1 OF 1		DATE		

Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.
 Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com