

PRODUCT DATA SHEET**QH9281W****Our patented 3 dB 90° Hybrid Couplers provide:**

- Superior component performance starting at 3:1 Bandwidth.
- Thicker center boards for high power and increased repeatability.
- Bonded structures which eliminate any air gaps between substrates.
- More sections per bandwidth for better coupling flatness.
- Electrically shorter and physically smaller RF components.

Features:

High Power Wide Bandwidths Small Size Connectorized Drop-In & Surface Mount

Electrical Specifications:

Frequency: 80 - 1000 MHz
Power: 250 W CW
Insertion Loss: 0.7 dB Max.
VSWR: 1.45:1 Max.
Phase Balance: $90^\circ \pm 5^\circ$ Max.
Amplitude Balance: ± 1.45 dB Max.
Isolation: 18 dB Min.

Mechanical Specifications:

Type: Connectorized
Material: Aluminum 6061-T6
Surface Finish: Chem. Film Per MIL-DTL-5541F Type I Class
3 Black Epoxy Paint/White Epoxy Lettering

Operating Temperature: -55°C to +75°C
Storage Temperature: -60°C to +85°C
Size: 4.55 x 3.18 x 1.0"

Connector Configurations:

Model	Sum Port (J1)	Inputs (J2,J3)
QH9281W-10	N Female	N Female

Werlatone's breakthrough technology allows us to build our existing line of Broadband 3 dB High Power 90° Hybrid Couplers. Connectorized 3 dB 90° Hybrid Coupler models are available with a choice of connectors. Several of our existing High Power 3 dB 90° RF Couplers are three port designs, wherein the difference port is internally terminated with a high power termination. This eliminates the need for a customer supplied external load for each Hybrid Coupler.



WERLATONE


Model QH9281W
90° Hybrids Connectorized

PRODUCT DATA SHEET


QH9281W

Performance Data (Specifications subject to change without notice):


Coupling:




VSWR:



Isolation:



Phase Balance:



Restriction on use, duplication, or disclosure of proprietary information. This document contains proprietary information which is the sole property of Werlatone, Inc.

Werlatone, Inc. 17 Jon Barrett Road Patterson, NY 12563 T:(845)278-2220 F:(845)278-3440 sales@werlatone.com www.werlatone.com

