



产品名称	接头形式	外径	最小弯曲半径	特性阻抗	插入损耗								最大驻波比
					1G	3G	6G	10G	18G	27G	40G	50G	
RG142	N,SMA,BNC	Ø4.95	25	50Ω			≤1.9						≤1.20
RG223	N,SMA,BNC	Ø5.3	25	50Ω			≤1.9						≤1.20
RG316	N,SMA,BNC	Ø2.52	13	50Ω		≤1.6							≤1.20
EB156	N,SMA	Ø5.15	40	50Ω					≤2.0				≤1.25
JC280	N,SMA	Ø2.8	28	50Ω					≤3.99				≤1.25
JA360	SMA,2.92mm,3.5mm	Ø3.6	36	50Ω							≤3.32		≤1.30
JB360	N,SMA,2.92mm	Ø3.6	36	50Ω							≤3.68		≤1.30
JB460	N,SMA	Ø4.6	46	50Ω					≤2.57				≤1.30
JA800	N,SMA,L29	Ø7.8	78	50Ω					≤1.18				≤1.25
GL18	N,SMA,3.5mm	Ø4.95	49.5	50Ω					≤2.67				≤1.25
GL26	SMA,3.5mm	Ø4.95	49.5	50Ω						≤3.42			≤1.30
GL18L	N,SMA,3.5mm	Ø4.6	46	50Ω					≤2.09				≤1.25
GL26L	SMA,3.5mm	Ø4.6	46	50Ω						≤2.57			≤1.30
PT40	2.92mm	Ø6.5	65	50Ω							≤3.68		≤1.30
PT50	2.4mm	Ø6.5	65	50Ω								≤4.13	≤1.35
SHX210	N,SMA	Ø5.5	50	50Ω					≤1.5				≤1.25
SHX3450	N	Ø7.4	25	50Ω					≤1.2				≤1.25
SHX3449	SMA	Ø4.8	29	50Ω						≤1.9			≤1.25
SHX3507	2.92mm,3.5mm	Ø3.6	38	50Ω							≤3.3		≤1.25
SHX3500	2.4mm	Ø3.1	25	50Ω								≤4.35	≤1.30
SR141	N,SMA,BNC	Ø3.58	13	50Ω				≤1.4					≤1.20
SF141	N,SMA,BNC	Ø3.58	40	50Ω			≤1.1						≤1.20
RG393	N,L29	Ø9.91	51	50Ω		≤0.5							≤1.20
1/2 波纹管	N,L29	Ø13.4	125	50Ω		≤0.7							≤1.20
MR400	N,L29,TNC	Ø10.3	100	50Ω		≤0.4							≤1.20
RG179	F	Ø2.54	10	75Ω	≤0.9								≤1.20
RG6	N,BNC	Ø7.07	70	75Ω	≤0.5								≤1.25

备注:

1. 所有外形尺寸单位 mm, 尺寸公差±5%
2. 可按照客户要求订制特殊规格接头和长度